

Affordable Vehicle GPS Tracker



**T366
Series**

2G/3G/4G network

Has three versions running on GSM, WCDMA and LTE Cat 1 networks respectively.

Flexible configurable I/O

Offer outstanding configuration flexibility to cater to a wide variety of requirements.

IP67 water resistant

Specialized design provides a tough casing that stands up to the elements.

Driving behavior analysis

Detect driver behaviors, such as the driver fatigue, idling, harsh acceleration/braking, harsh cornering, collision, etc.



APPLICATION



Off-road vehicle



Fire engine



Beach buggy



Yacht

SPECIFICATIONS

ITEM	SPECIFICATIONS
Dimension	80.5 mm x 60 mm x 23.5 mm
Weight	100g
I/O power cable length	50cm
Power supply	DC 11.4–90 V/1.5 A
Power consumption	Current in standby mode: 65 mA
Operating temperature	-35°C to 80°C (available for the device without a battery)
Operating humidity	5% to 95%
LED indicator	Green indicator showing the 2G/3G/4G signal Blue indicator showing the GPS signal
Button/Switch	1 upgrade button (used to manually upgrade the firmware) 1 power button
Memory	8 MB buffer
Sensor	3-axis accelerometer (used to wake the device up by vibration and detect towing alerts, harsh acceleration alerts, and harsh braking alerts)
GNSS	GPS/GLONASS/BeiDou/Galileo
Positioning accuracy	2.5m
I/O port	2 x Din, 1 x Dout, 1 x AD, 1 x 1-wire, 1 x RS232, 1 x 5V_out
Frequency band	T366: GSM/GPRS: 850/900/1800/1900 MHz
	T366L: T366L-E: LTE FDD: B1/B3/B7/B8/B20/B28A, WCDMA: B1/B8, GSM/GPRS: B3/B8 T366L-A: LTE FDD: B2/B4/B12, WCDMA: B2/B4/B5 T366L-AU: LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28, LTE TDD: B40, WCDMA: B1/B2/B5/B8, GSM/GPRS: B2/B3/B5/B8 T366L-AUT: LTE FDD: B1/B3/B5/B7/B28, WCDMA: B1/B5 T366L-G: LTE FDD: B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28, LTE TDD: B38/B39/B40/B41, WCDMA: B1/B2/B4/B5/B6/B8/B19, GSM/GPRS: B2/B3/B5/B8



T366 Series Tracker
L wrench
Hexagon screw
400 mAh battery
CD download card

ACCESSORIES



OPTIONAL ACCESSORIES

A52 digital temperature sensor
A53 fuel level sensor
A57 speaker
A58 microphone
A64 remote control receiver
A67 remote control
Relay (12 V/24 V)
External GPS antenna
Ultrasonic fuel level sensor
RFID
Buzzer
USB cable
iButton reader



RoHS



NBTC



+86(755)83462818



www.meitrack.com



info@meitrack.com



5/F, International Internet Finance Pioneer Park, No. 1, Taohua Rd.,
Futian Free Trade Zone, Shenzhen, China. 518038