

BLE Vehicle GNSS Tracker



**T399
Series**



Bluetooth Communication

Support Bluetooth temperature and humidity sensor and multiple beacons at one time.

Flexible Configurable I/O

Offer outstanding configuration flexibility to cater to a wide variety of requirements.

IP67 Water Resistant

Specialized design provides a tough casing that stands up to the elements.

Driving Behavior Analysis

Detect driver behaviors, such as the driver fatigue, idling, harsh acceleration/braking, harsh cornering, collision, etc.

APPLICATION



Cold Chain Trucks



Off-road Vehicles



Emergency Vehicles



Aquatic Vehicles

SPECIFICATIONS

ITEM	SPECIFICATIONS
Dimension	80.5 mm x 60 mm x 23.5 mm
Weight	100g
I/O power cable length	50cm
Power supply	DC 11.4–90 V/1.5 A
Battery	Internal 400 mAh battery (normal temperature resistant: -20°C to 60°C)
Power consumption	Current in standby mode: 65 mA
Operating temperature	-35°C to 80°C (available for the device without a battery) -5°C to 75°C (available for the device with a high temperature resistant battery)
Operating humidity	5% to 95%
LED indicator	Green LED indicator showing the network signal Blue LED indicator showing the GPS signal
Button/Switch	1 upgrade button (used to manually upgrade the firmware) 1 power button
Memory	8 MB buffer
Sensor	3-axis accelerometer (used to wake the device up by vibration and detect towing alerts, harsh acceleration alerts, and harsh braking alerts)
GNSS	GPS/GLONASS/BeiDou/Galileo
Positioning accuracy	2.5m
Bluetooth	Support Bluetooth 4.2 and Bluetooth 5.0
GPS/GSM antenna	Built-in antenna
I/O port	4 x Din/AD, 1 x Dout, 1 x 1-wire, 1 x 5V_out, 1 x RS232
Frequency band	T399L-EA: FDD: B1/B3/B7/B8/B20/B28, TDD: B38/B40, WCDMA: B1/B8, GSM: 900/1800MHz
	T399L-ER: FDD: B1/B3/B5/B7/B8/B20/B28, TDD: B38/B40/B41 GSM: B2/B3/B5/B8
	T399L-AUR: FDD: B1/B2/B3/B4/B5/B7/B8/B28/B66, TDD: B38/B40/B41 GSM: B2/B3/B5/B8
	T399G: WCDMA: B1/B2/B5/B8, GSM: B2/B3/B5/B8
	T399E: CAT M1/NB: B1/B2/B3/B4/B5/B8/B12/B13/B14/B18/ B19/B20/B25/B26/B27/B28/B66/B71/B85 GSM: 850/900/1800/1900MHzLTE



T399 Series tracker
L wrench
Hexagon screw
CD download card

ACCESSORIES



OPTIONAL ACCESSORIES

Relay (12 V/24 V)
Ultrasonic fuel level sensor
A52 digital temperature sensor
A53 fuel level sensor
Bluetooth temperature and humidity sensor
High temperature resistant battery (400 mAh)

USB cable
iButton reader
External GPS antenna
Buzzer
Bluetooth beacon
RFID reader



+86(755)83462818



www.meitrack.com



info@meitrack.com



5/F, International Internet Finance Pioneer Park, No. 1, Taohua Rd.,
Futian Free Trade Zone, Shenzhen, China. 518038